

### SECTION 1: IDENTIFICATION

#### 1.1. Product Identifier

**Product Form:** Mixture

**Product Name:** Sandstone

**Synonyms:** Aggregates, Asphalt Sand, Base Material, Concrete Sand, Crushed Rock, Crushed Stone, Crushed Run, Dense Graded Aggregate, Fill Sand, Golf Course Sand, Gravel, Manufactured Sand, Mason Sand

**Note:** This MSDS covers many types of sandstone. Individual composition of hazardous constituents will vary between types of sandstone.

#### 1.2. Intended Use of the Product

Sandstone is used in the manufacture of bricks, cement, concrete, mortar, paving materials, plasters, and other construction applications. Sandstone is distributed in bags, totes and bulk shipment.

#### 1.3. Name, Address, and Telephone of the Responsible Party

##### Company

LafargeHolcim in the US

8700 West Bryn Mawr Avenue, Suite 300

Chicago, IL 60631

Information: (888) 646-5246 (9am to 5pm CST)

Email: [us-sds-inquiries@lafargeholcim.com](mailto:us-sds-inquiries@lafargeholcim.com)

Website: [www.MaterialsThatPerform.com](http://www.MaterialsThatPerform.com)

The LafargeHolcim companies in the US include Holcim (US)

Inc., Aggregate Industries Management Inc., and their subsidiaries and affiliates.

#### 1.4. Emergency Telephone Number

**Emergency Number** : CHEMTREC 1-800-424-9300 (24 hours)

### SECTION 2: HAZARDS IDENTIFICATION

#### 2.1. Classification of the Substance or Mixture

##### GHS-US/CA Classification

Carc. 1A H350

STOT SE 3 H335

STOT RE 1 H372

Full text of hazard classes and H-statements : see section 16

#### 2.2. Label Elements

##### GHS-US/CA Labeling

##### Hazard Pictograms (GHS-US/CA)



##### Signal Word (GHS-US/CA)

: Danger

##### Hazard Statements (GHS-US/CA)

: H335 - May cause respiratory irritation.

H350 - May cause cancer (Inhalation).

H372 - Causes damage to organs (lung/respiratory system) through prolonged or repeated exposure (Inhalation).

##### Precautionary Statements (GHS-US/CA)

: P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P260 - Do not breathe dust.

P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product.

P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear protective gloves, protective clothing, and eye protection.

# Sandstone

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P308+P313 - If exposed or concerned: Get medical advice/attention.

P312 - Call a POISON CENTER or doctor if you feel unwell.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P405 - Store locked up.

P501 - Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

### 2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions. Repeated or prolonged exposure to respirable (airborne) crystalline silica dust will cause lung damage in the form of silicosis. Symptoms will include progressively more difficult breathing, cough, fever, and weight loss.

### 2.4. Unknown Acute Toxicity (GHS-US/CA)

No data available

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Synonyms	Product Identifier	% *	GHS Ingredient Classification
Quartz	Quartz (SiO <sub>2</sub> ) / Silica, crystalline, quartz / Crystalline silica, quartz / .alpha.-Quartz / Silica, crystalline, .alpha.-quartz / Crystalline silica in the form of quartz / Quartz, silica / Quartz (respirable fraction) / Silica dust / Silica, crystalline-.alpha.quartz / Silica, quartz / Silica, .alpha.-quartz / Silicon dioxide / Silica, crystalline / Quartz (crystalline silica) / Silica dust, crystalline / QUARTZ POWDER / Silica, crystalline (quartz)	(CAS-No.) 14808-60-7	85 – 100	Carc. 1A, H350 STOT SE 3, H335 STOT RE 1, H372
Mica	Mica dust / Mica group minerals / Mica, respirable / Silicates, mica / C.I. 77019 / Mica-group minerals / C.I. Pigment White 20	(CAS-No.) 12001-26-2	< 5	Not classified

Full text of H-phrases: see section 16

\*Percentages are listed in weight by weight percentage (w/w%) for liquid and solid ingredients. Gas ingredients are listed in volume by volume percentage (v/v%).

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of First-aid Measures

**General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

**Inhalation:** When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

**Skin Contact:** Remove contaminated clothing. Drench affected area with water for at least 15 minutes. If exposed or concerned: Get medical advice/attention.

**Eye Contact:** Rinse cautiously with water for at least 5 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if irritation develops or persists.

**Ingestion:** Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

### 4.2. Most Important Symptoms and Effects Both Acute and Delayed

**General:** May cause respiratory irritation. Causes damage to organs (lung/respiratory system) (Inhalation). May cause cancer by inhalation.

**Inhalation:** Irritation of the respiratory tract and the other mucous membranes. Some studies show that exposure to respirable crystalline silica (without silicosis) or that the disease silicosis may be associated with the increased incidence of several autoimmune disorders such as scleroderma (thickening of the skin), systemic lupus erythematosus, rheumatoid arthritis and diseases affecting the kidneys. Silicosis increases the risk of tuberculosis. Some studies show an increased incidence of chronic kidney disease and end-stage renal disease in workers exposed to respirable crystalline silica.

**Skin Contact:** Skin contact with large amounts of dust may cause mechanical irritation.

# Sandstone

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

**Eye Contact:** Eye contact with dust may cause mechanical irritation.

**Ingestion:** Ingestion may cause adverse effects.

**Chronic Symptoms:** Long term exposure to respirable crystalline silica results in a significant risk of developing silicosis and other non-malignant respiratory disease, lung cancer, kidney effects, and immune system effects.

### 4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

## SECTION 5: FIRE-FIGHTING MEASURES

### 5.1. Extinguishing Media

**Suitable Extinguishing Media:** Use extinguishing media suitable for surrounding type of fire.

**Unsuitable Extinguishing Media:** None known.

### 5.2. Special Hazards Arising From the Substance or Mixture

**Fire Hazard:** Not flammable.

**Explosion Hazard:** Product is not explosive.

**Reactivity:** Hazardous reactions will not occur under normal conditions.

### 5.3. Advice for Firefighters

**Precautionary Measures Fire:** Exercise caution when fighting any chemical fire.

**Firefighting Instructions:** Use water spray or fog for cooling exposed containers.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.

**Hazardous Combustion Products:** Silicon oxides.

### 5.4. Reference to Other Sections

Refer to Section 9 for flammability properties.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal Precautions, Protective Equipment and Emergency Procedures

**General Measures:** Do not handle until all safety precautions have been read and understood. Avoid creating dusty conditions whenever feasible. Do not breathe dust. Do not get in eyes, on skin, or on clothing.

#### 6.1.1. For Non-Emergency Personnel

**Protective Equipment:** Use appropriate personal protective equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel.

#### 6.1.2. For Emergency Personnel

**Protective Equipment:** Equip cleanup crew with proper protection.

**Emergency Procedures:** Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area.

### 6.2. Environmental Precautions

Prevent entry to sewers and public waters.

### 6.3. Methods and Materials for Containment and Cleaning Up

**For Containment:** Contain solid spills with appropriate barriers and prevent migration and entry into sewers or streams.

**Methods for Cleaning Up:** Clean up spills immediately and dispose of waste safely. Recover the product by vacuuming, shoveling or sweeping. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

### 6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

## SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for Safe Handling

**Additional Hazards When Processed:** Stack bagged material in a secure manner to prevent falling. Bagged aggregate is heavy and poses risks such as sprains and strains to the back, arms, shoulders and legs during lifting and mixing. Handle with care and use appropriate control measures. Cutting, crushing or grinding crystalline silica-bearing materials may release respirable crystalline silica, a known carcinogen. Use all appropriate measures of dust control or suppression and Personal Protective.

**Precautions for Safe Handling:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid contact with eyes, skin and clothing. Do not breathe dust. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures.

# Sandstone

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

### 7.2. Conditions for Safe Storage, Including Any Incompatibilities

**Technical Measures:** Comply with applicable regulations.

**Storage Conditions:** Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from Incompatible materials. Store locked up/in a secure area.

**Incompatible Materials:** Dissolves in hydrofluoric acid, producing corrosive silicon tetrafluoride gas. Silicates react with powerful oxidizers such as fluorine, boron trifluoride, chlorine trifluoride, manganese trifluoride, and oxygen difluoride.

**Storage Temperature:** Unlimited

### 7.3. Specific End Use(s)

Sandstone is used in the manufacture of bricks, cement, concrete, mortar, paving materials, plasters, and other construction applications. Sandstone is distributed in bags, totes and bulk shipment.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), or Canadian provincial governments.

Quartz (14808-60-7)		
USA ACGIH	ACGIH OEL TWA	0.025 mg/m <sup>3</sup> (respirable particulate matter)
USA ACGIH	ACGIH chemical category	A2 - Suspected Human Carcinogen
USA OSHA	OSHA PEL TWA	50 µg/m <sup>3</sup> (Respirable crystalline silica)
USA OSHA	OSHA PEL TWA	(250)/(%SiO <sub>2</sub> +5) mppcf TWA (respirable fraction) (10)/(%SiO <sub>2</sub> +2) mg/m <sup>3</sup> TWA (respirable fraction) (For any operations or sectors for which the respirable crystalline silica standard, 1910.1053, is stayed or otherwise not in effect, See 20 CFR 1910.1000 TABLE Z-3)
USA NIOSH	NIOSH REL TWA	0.05 mg/m <sup>3</sup> (respirable dust)
USA IDLH	IDLH	50 mg/m <sup>3</sup> (respirable dust)
Alberta	OEL TWA	0.025 mg/m <sup>3</sup> (respirable particulate)
British Columbia	OEL TWA	0.025 mg/m <sup>3</sup> (respirable)
Manitoba	OEL TWA	0.025 mg/m <sup>3</sup> (respirable particulate matter)
New Brunswick	OEL TWA	0.1 mg/m <sup>3</sup> (respirable fraction)
Newfoundland & Labrador	OEL TWA	0.025 mg/m <sup>3</sup> (respirable particulate matter)
Nova Scotia	OEL TWA	0.025 mg/m <sup>3</sup> (respirable particulate matter)
Nunavut	OEL TWA	0.05 mg/m <sup>3</sup> (respirable fraction (Silica - crystalline))
Northwest Territories	OEL TWA	0.05 mg/m <sup>3</sup> (respirable fraction (Silica - crystalline))
Ontario	OEL TWA	0.1 mg/m <sup>3</sup> (designated substances regulation-respirable fraction (Silica, crystalline))
Prince Edward Island	OEL TWA	0.025 mg/m <sup>3</sup> (respirable particulate matter)
Québec	VEMP OEL TWA	0.1 mg/m <sup>3</sup> (respirable dust)
Saskatchewan	OEL TWA	0.05 mg/m <sup>3</sup> (respirable fraction (Silica - crystalline (Trydimite removed)))
Yukon	OEL TWA	300 particle/mL (Silica - Quartz, crystalline)
Mica (12001-26-2)		
USA ACGIH	ACGIH OEL TWA	3 mg/m <sup>3</sup> (respirable particulate matter)
USA OSHA	OSHA PEL TWA	20 mppcf (<1% Crystalline silica) (See 20 CFR 1910.1000 TABLE Z-3)
USA NIOSH	NIOSH REL TWA	3 mg/m <sup>3</sup> (containing <1% Quartz-respirable dust)
USA IDLH	IDLH	1500 mg/m <sup>3</sup> (containing <1% quartz)
Alberta	OEL TWA	3 mg/m <sup>3</sup> (respirable)
British Columbia	OEL TWA	3 mg/m <sup>3</sup> (respirable)
Manitoba	OEL TWA	3 mg/m <sup>3</sup> (respirable particulate matter)
New Brunswick	OEL TWA	3 mg/m <sup>3</sup> (particulate matter containing no Asbestos and <1% Crystalline silica, respirable fraction)
Newfoundland & Labrador	OEL TWA	3 mg/m <sup>3</sup> (respirable particulate matter)

# Sandstone

## Safety Data Sheet


According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Nova Scotia	OEL TWA	3 mg/m <sup>3</sup> (respirable particulate matter)
Nunavut	OEL STEL	6 mg/m <sup>3</sup> (respirable fraction)
Nunavut	OEL TWA	3 mg/m <sup>3</sup> (respirable fraction)
Northwest Territories	OEL STEL	6 mg/m <sup>3</sup> (respirable fraction)
Northwest Territories	OEL TWA	3 mg/m <sup>3</sup> (respirable fraction)
Ontario	OEL TWA	3 mg/m <sup>3</sup> (respirable particulate matter)
Prince Edward Island	OEL TWA	3 mg/m <sup>3</sup> (respirable particulate matter)
Québec	VEMP OEL TWA	3 mg/m <sup>3</sup> (containing no Asbestos and <1% Crystalline silica-respirable dust)
Saskatchewan	OEL STEL	6 mg/m <sup>3</sup> (respirable fraction)
Saskatchewan	OEL TWA	3 mg/m <sup>3</sup> (respirable fraction)
Yukon	OEL TWA	20 mppcf

### 8.2. Exposure Controls

**Appropriate Engineering Controls:** Ensure adequate ventilation, especially in confined areas. Suitable eye/body wash equipment should be available in the vicinity of any potential exposure. Ensure all national/local regulations are observed.

**Personal Protective Equipment:** Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.



**Materials for Protective Clothing:** Chemically resistant materials and fabrics.

**Hand Protection:** Wear protective gloves.

**Eye and Face Protection:** Chemical safety goggles.

**Skin and Body Protection:** Wear suitable protective clothing.

**Respiratory Protection:** If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

**Other Information:** When using, do not eat, drink or smoke.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on Basic Physical and Chemical Properties

Physical State	: Solid
Appearance	: Variety of colors
Odor	: None
Odor Threshold	: Not available
pH	: Neutral
Evaporation Rate	: Not available
Melting Point	: Not available
Freezing Point	: None, solid
Boiling Point	: > 1000 °C (1832 °F)
Flash Point	: Not available
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not available
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: Not available
Relative Vapor Density at 20°C	: Not available
Relative Density	: Not available
Specific Gravity	: 2.5 - 2.7 (water=1)
Solubility	: Insoluble in water.

# Sandstone

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

**Partition Coefficient: N-Octanol/Water** : Not available  
**Viscosity** : None, solid

### SECTION 10: STABILITY AND REACTIVITY

- 10.1. Reactivity:** Hazardous reactions will not occur under normal conditions.  
**10.2. Chemical Stability:** Stable under recommended handling and storage conditions (see section 7).  
**10.3. Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.  
**10.4. Conditions to Avoid:** Incompatible materials.  
**10.5. Incompatible Materials:** Dissolves in hydrofluoric acid, producing corrosive silicon tetrafluoride gas. Silicates react with powerful oxidizers such as fluorine, boron trifluoride, chlorine trifluoride, manganese trifluoride, and oxygen difluoride.  
**10.6. Hazardous Decomposition Products:** Thermal decomposition may produce: Silicon oxides.

### SECTION 11: TOXICOLOGICAL INFORMATION

#### 11.1. Information on Toxicological Effects - Product

- Acute Toxicity (Oral):** Not classified  
**Acute Toxicity (Dermal):** Not classified  
**Acute Toxicity (Inhalation):** Not classified  
**LD50 and LC50 Data:** Not available  
**Skin Corrosion/Irritation:** Not classified  
**pH:** Neutral  
**Eye Damage/Irritation:** Not classified  
**pH:** Neutral  
**Respiratory or Skin Sensitization:** Not classified  
**Germ Cell Mutagenicity:** Not classified  
**Carcinogenicity:** May cause cancer (Inhalation).  
**Specific Target Organ Toxicity (Repeated Exposure):** Causes damage to organs (lung/respiratory system) through prolonged or repeated exposure (Inhalation).  
**Reproductive Toxicity:** Not classified  
**Specific Target Organ Toxicity (Single Exposure):** May cause respiratory irritation.  
**Aspiration Hazard:** Not classified  
**Symptoms/Injuries After Inhalation:** Irritation of the respiratory tract and the other mucous membranes. Some studies show that exposure to respirable crystalline silica (without silicosis) or that the disease silicosis may be associated with the increased incidence of several autoimmune disorders such as scleroderma (thickening of the skin), systemic lupus erythematosus, rheumatoid arthritis and diseases affecting the kidneys. Silicosis increases the risk of tuberculosis. Some studies show an increased incidence of chronic kidney disease and end-stage renal disease in workers exposed to respirable crystalline silica.  
**Symptoms/Injuries After Skin Contact:** Skin contact with large amounts of dust may cause mechanical irritation.  
**Symptoms/Injuries After Eye Contact:** Eye contact with dust may cause mechanical irritation.  
**Symptoms/Injuries After Ingestion:** Ingestion may cause adverse effects.  
**Chronic Symptoms:** Long term exposure to respirable crystalline silica results in a significant risk of developing silicosis and other non-malignant respiratory disease, lung cancer, kidney effects, and immune system effects.

#### 11.2. Information on Toxicological Effects - Ingredient(s)

**LD50 and LC50 Data:**

<b>Quartz (14808-60-7)</b>	
<b>LD50 Oral Rat</b>	> 5000 mg/kg
<b>LD50 Dermal Rat</b>	> 5000 mg/kg
<b>Quartz (14808-60-7)</b>	
<b>IARC Group</b>	1
<b>National Toxicology Program (NTP) Status</b>	Known Human Carcinogens.
<b>OSHA Hazard Communication Carcinogen List</b>	In OSHA Hazard Communication Carcinogen list.

### SECTION 12: ECOLOGICAL INFORMATION

#### 12.1. Toxicity

**Ecology - General:** Not classified.

# Sandstone

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

### 12.2. Persistence and Degradability

Sandstone	
Persistence and Degradability	Not established.

### 12.3. Bioaccumulative Potential

Sandstone	
Bioaccumulative Potential	Not established.

12.4. Mobility in Soil Not available

### 12.5. Other Adverse Effects

Other Information: Avoid release to the environment.

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

**Waste Disposal Recommendations:** Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

**Ecology - Waste Materials:** Avoid release to the environment.

## SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

14.1. In Accordance with DOT Not regulated for transport

14.2. In Accordance with IMDG Not regulated for transport

14.3. In Accordance with IATA Not regulated for transport

14.4. In Accordance with TDG Not regulated for transport

## SECTION 15: REGULATORY INFORMATION

### 15.1. US Federal Regulations

Sandstone	
SARA Section 311/312 Hazard Classes	Health hazard - Specific target organ toxicity (single or repeated exposure) Health hazard - Carcinogenicity
Quartz (14808-60-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

### 15.2. US State Regulations

#### California Proposition 65



**WARNING:** This product can expose you to Quartz, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Chemical Name (CAS No.)	Carcinogenicity	Developmental Toxicity	Female Reproductive Toxicity	Male Reproductive Toxicity
Quartz (14808-60-7)	X			

#### Quartz (14808-60-7)

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

U.S. - Massachusetts - Right To Know List

#### Mica (12001-26-2)

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

U.S. - Massachusetts - Right To Know List

### 15.3. Canadian Regulations

#### Quartz (14808-60-7)

Listed on the Canadian DSL (Domestic Substances List)

#### Mica (12001-26-2)

Listed on the Canadian DSL (Domestic Substances List)

# Sandstone

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

### SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

**Date of Preparation or Latest Revision** : 06/14/2021

**Other Information** : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200 and Canada's Hazardous Products Regulations (HPR) SOR/2015-17.

#### GHS Full Text Phrases:

Carc. 1A	Carcinogenicity Category 1A
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H335	May cause respiratory irritation
H350	May cause cancer
H372	Causes damage to organs through prolonged or repeated exposure

*LafargeHolcim in the US believes the information contained herein is accurate; however, LafargeHolcim in the US makes no guarantees with respect to such accuracy and assumes no liability in connection with the use of the information contained herein which is not intended to be and should not be construed as legal advice or as insuring compliance with any federal, state or local laws or regulations. Any party using this product should review all such laws, rules, or regulations prior to use, including but not limited to US and Canada Federal, Provincial and State regulations.*

**NO WARRANTY IS MADE, EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR OTHERWISE.**

NA GHS SDS 2015 (Can, US)