

### 1. Product Name

- Mortamix® Rainbow Custom Color Masonry Cement™

### 2. Manufacturer

Holcim (US) Inc.  
8700 Bryn Mawr Avenue  
Chicago, IL 60631  
Phone: (888) 646-5246  
E-mail: [ask@holcim.com](mailto:ask@holcim.com)  
Web: [www.holcim.us](http://www.holcim.us)

### 3. Product Description

#### Usage

Mortamix® Rainbow Custom Color Masonry Cement™ is a formulated cementitious material manufactured to be used in producing masonry mortars for brick, block and stone masonry units. Mortamix® Rainbow Custom Color Masonry Cement™ also can be used to produce stucco, a versatile facing material that can be applied to wall or ceiling surfaces to achieve special architectural finishes. Mortamix® Rainbow Custom Color Masonry Cement™ can be custom blended to color match and/or complement any architectural accent or specified masonry unit.

#### Composition and Materials

Mortamix® Rainbow Custom Color Masonry Cement™ is a combination of portland cement, plasticizers, ground limestone, air entraining additives and inorganic oxide color pigments. The above ingredients are combined and processed at Holcim (US) Inc. manufacturing facilities under controlled conditions to ensure uniform conformance.

#### Types

Mortamix® Rainbow Custom Color Masonry Cement™ is produced to meet ASTM C91, standard specification requirements for Type N, Type S or Type M masonry cements. When mixed with proper proportion of sand (meeting ASTM C144) and clean water, the resulting mortar conforms to the property specifications of ASTM C270 for Type N, Type S or Type M mortar.

While climate conditions, exposure and engineering requirements must be considered, Type N mortar is recommended for above-grade interior and exterior load-bearing and non-load bearing walls. Type S and M mortars are a higher compressive strength and are recommended for below grade walls and load-bearing walls where higher compressive strengths are needed.



*Mortamix® Rainbow Custom Color Masonry Cement™ used on Naples Daily News Building*

#### Sizes

Mortamix® Rainbow Custom Color Masonry Cement™ is available in the following packaging sizes (bags):

- **Type N** 32 kilogram (70.5 pound)
- **Type S** 34 kilogram (75 pound)
- **Type M** 32 kilogram (79.4 pound)

#### Colors

Mortamix® Rainbow Custom Color Masonry Cement™ is available in many standard colors, including white. In addition, colors can be custom formulated under laboratory conditions to match desired customer specifications.

#### Benefits

Meets ASTM C91 for Type N, S, or M masonry cement.



## 4. Technical Data

### Applicable Standards

- **ASTM C91** Standard Specification for Masonry Cement
- **ASTM C144** Standard Specification for Aggregate for Masonry Mortar
- **ASTM C270** Standard Specification for Mortar for Unit Masonry

### Physical / Chemical Properties

Each type of Mortamix® Rainbow Custom Color Masonry Cement™ conforms to ASTM C91.

- Type N, Type S and Type M Mortamix® Rainbow Custom Color Masonry Cement™ are used to produce ASTM C270 Type N, Type S or Type M mortar, respectively.
- Requirements for sand to be used in conjunction with these products are outlined in ASTM C144.

## 5. Installation

### Preparatory Work

Mortamix® Rainbow Custom Color Masonry Cement™ should be mixed according to ASTM C270. Machine mixing is highly recommended. Mixing instructions are printed on each bag and shown below:

- Use 1 bag Mortamix® Rainbow Custom Color Masonry Cement™ to 2-1/4 to 3 parts damp loose sand by volume. Sand requirements are outlined in ASTM C144.

### Batching Sequence:

- First add approximately 3/4 of the desired volume of mix water; then add 1/2 the sand followed by 1 bag of Mortamix® Rainbow Custom Color Masonry Cement™ to the mixer.
- Finally, add the rest of the sand and remaining mix water sufficient to achieve the desired field workability.
- The combined materials should be mixed 3-5 minutes after all materials are in the mixer.

### Precautions

- Never change sand sources or mortar mixture proportion volumes during the project; undesirable color changes and performance changes to the finished product could result.
- Holcim (US) Inc. does not recommend the use of any other additives or admixtures.
- Tool all joints to the same degree of firmness in a uniform consistent manner.
- Avoid excessive re-tempering, which could result in color variations.
- Protect masonry units from weather before and after they are set in place.
- Holcim (US) Inc. does not recommend the use of acid-based cleaning solutions.
- To verify finished appearance, Holcim (US) Inc. always recommends that a job specific sample panel be erected; using the same sand, masonry units and construction practice used on your project.

### Safety Precautions

Refer to the applicable Safety Data Sheet (SDS), which should be consulted prior to the use of this product. These SDS's are available at [www.holcim.us](http://www.holcim.us).

Avoid direct contact with the skin. If contact occurs, wash skin with water as soon as possible. Exposure of sufficient duration to Mortamix® Rainbow Custom Color Masonry Cement™ can cause serious and potentially irreversible tissue destruction in the form of chemical burns. If masonry cement gets into the eyes, immediately flush eyes thoroughly with water and seek medical attention. Proper PPE is always required.

### Storage and Handling

Packaged masonry cements needing to be temporarily stored on construction sites should be stored above the ground on pallets or other means that allow airflow between the ground and the stored packaged material. Tarps or polyethylene sheeting should cover the material when not in use to prevent moisture, precipitation or high humidity from coming in contact with the bags. Prevent storage directly against walls or other structures and allow pallets to have an adequate space to allow for air circulation to reduce moisture accumulations. Construction sites and weather conditions vary and further measures may be required to protect products from moisture.

## 6. Availability and Cost

Availability: Mortamix® Rainbow Custom Color Masonry Cement™ is regionally available. Contact the nearest Holcim (US) Inc. sales office for availability in your area.

Cost: Pricing information can be obtained from the nearest Holcim (US) Inc. sales office.

## 7. Warranty

Upon request, Holcim (US) Inc. can provide Material Certification Reports demonstrating that Mortamix® Rainbow Custom Color Masonry Cement™ meets applicable ASTM standards. Holcim (US) Inc. will not guarantee finish work, having no control over the use of this product. Holcim (US) Inc. shall not be responsible for condition of cement after delivering to dealer or distributor.

## 8. Technical Services

Technical service is available by contacting the nearest Holcim (US) Inc. sales office at (888) 646-5246.

For questions on any technical information contained in this document, contact a Holcim (US) Inc. Technical Service Engineer for further detail.

## 9. Filing Systems

Additional product information is available from the manufacturer.

### Corporate Headquarters

Holcim (US) Inc.  
8700 Bryn Mawr Avenue  
Chicago, IL 60631  
(888) 646-5246

### Corporate Office

6211 Ann Arbor Road  
P.O. Box 122  
Dundee, MI 48131  
(888) 646-5246