

SECTION 1: IDENTIFICATION

1.1. Product Identifier

Product Form: Mixture

Product Name: Hydrated Lime

Synonyms: Calcium Dihydroxide, Calcium Hydroxide, Calcium Magnesium Hydroxide, Caustic Lime, Dolomitic Hydrated Lime, Lafarge Hydrated Lime, Lime, Lime Hydrate, Slaked Lime, Type N Lime, Type S Lime

Note: This SDS covers many types of hydrated lime. Individual composition of hazardous constituents will vary between types of hydrated lime.

1.2. Intended Use of the Product

Hydrated lime is used as an additive for mortar, cement, concrete and concrete products. It is also used in soil stabilization, as an anti-stripping agent in asphalt, for pH adjustment, and in other products that are widely used in construction.

1.3. Name, Address, and Telephone of the Responsible Party

Company

Holcim US

8700 West Bryn Mawr Avenue, Suite 300

Chicago, IL 60631

Information: (888) 646-5246 (9am to 5pm CST)

Email: us-sds-inquiries@holcim.com

Website: holcim.us

1.4. Emergency Telephone Number

Emergency Number : ChemTel LLC

1-800-255-3924 (US and Canada)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

GHS-US/CA Classification

Skin Irrit. 2 H315

Eye Dam. 1 H318

Carc. 1A H350

STOT SE 3 H335

Full text of hazard classes and H-statements : see section 16

2.2. Label Elements

GHS-US/CA Labeling

Hazard Pictograms (GHS-US/CA)



Signal Word (GHS-US/CA)

: Danger

Hazard Statements (GHS-US/CA)

: H315 - Causes skin irritation.

H318 - Causes serious eye damage.

H335 - May cause respiratory irritation.

H350 - May cause cancer (Inhalation).

Precautionary Statements (GHS-US/CA)

: P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P261 - Avoid breathing dust.

P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.

P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear protective gloves, protective clothing, and eye protection.

Hydrated Lime

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

P302+P352 - IF ON SKIN: Wash with plenty of water.
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 - If exposed or concerned: Get medical advice/attention.
P310 - Immediately call a POISON CENTER or doctor.
P321 - Specific treatment (see section 4 on this SDS).
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P405 - Store locked up.
P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations.

2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions. Repeated or prolonged exposure to respirable (airborne) crystalline silica dust will cause lung damage in the form of silicosis. Symptoms will include progressively more difficult breathing, cough, fever, and weight loss.

2.4. Unknown Acute Toxicity (GHS-US/CA)

No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

3.2. Mixture

| Name | Synonyms | Product Identifier | % * | GHS Ingredient Classification |
|-----------------------|--|----------------------|---------|--|
| Calcium hydroxide | Calcium dihydroxide / Calcium hydroxide (Ca(OH) ₂) / Hydrated lime / Lime, hydrated / CALCIUM HYDROXIDE / Slaked lime | (CAS-No.) 1305-62-0 | 50 – 95 | Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 |
| Magnesium hydroxide | Magnesium dihydroxide / Magnesium hydroxide (Mg(OH) ₂) / MAGNESIUM HYDROXIDE / Milk of magnesia | (CAS-No.) 1309-42-8 | ≤ 50 | Not classified |
| Magnesium oxide (MgO) | Calcined magnesite / Magnesium oxide / MAGNESIUM OXIDE / Magnesia | (CAS-No.) 1309-48-4 | ≤ 5 | Not classified |
| Calcium oxide | Lime / Quicklime / Quicklime (CaO) / Calcium oxide (CaO) / Lime (calcium oxide) | (CAS-No.) 1305-78-8 | ≤ 5 | Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 3, H402 Aquatic Chronic 3, H412 |
| Limestone | Chalk / Limestone (A noncombustible solid characteristic of sedimentary rock. It consists primarily of calcium carbonate.) / Natural calcium carbonate / Marble / Calcium carbonate / Limestone (sedimentary rock) / Calcite / Limestone ground / Acetate, 4-methyl-2-propyl-2H-tetrahydropyran-4-yl / Ground limestone | (CAS-No.) 1317-65-3 | ≤ 3 | Not classified |
| Quartz | Quartz (SiO ₂) / Silica, crystalline, quartz / Crystalline silica, quartz / .alpha.-Quartz / QUARTZ / Silica, crystalline, .alpha.-quartz / Crystalline silica in the form of quartz / Quartz, silica / Quartz (respirable fraction) / Silica dust / Silica, crystalline-.alpha.quartz / Silica, quartz / Silica, .alpha.-quartz / Silicon dioxide / Silica, crystalline / Quartz (crystalline silica) / Silica dust, crystalline / QUARTZ POWDER / Silica, crystalline (quartz) | (CAS-No.) 14808-60-7 | ≤ 1 | Carc. 1A, H350 STOT SE 3, H335 STOT RE 1, H372 |

Full text of H-phrases: see section 16

*Percentages are listed in weight by weight percentage (w/w%) for liquid and solid ingredients. Gas ingredients are listed in volume by volume percentage (v/v%).

Hydrated Lime

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

SECTION 4: FIRST AID MEASURES

4.1. Description of First-aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Inhalation: When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

Skin Contact: Remove contaminated clothing. Immediately drench affected area with water for at least 15 minutes. If exposed or concerned: Get medical advice/attention.

Eye Contact: Immediately rinse with water for at least 30 minutes. Rinse cautiously with water for at least 60 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention. Remove contact lenses, if present and easy to do. Continue rinsing.

Ingestion: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Obtain medical attention.

4.2. Most Important Symptoms and Effects Both Acute and Delayed

General: May cause respiratory irritation. Causes skin irritation. Causes serious eye damage. May cause cancer by inhalation.

Inhalation: Irritation of the respiratory tract and the other mucous membranes. Some studies show that exposure to respirable crystalline silica (without silicosis) or that the disease silicosis may be associated with the increased incidence of several autoimmune disorders such as scleroderma (thickening of the skin), systemic lupus erythematosus, rheumatoid arthritis and diseases affecting the kidneys. Silicosis increases the risk of tuberculosis. Some studies show an increased incidence of chronic kidney disease and end-stage renal disease in workers exposed to respirable crystalline silica.

Skin Contact: Redness, pain, swelling, itching, burning, dryness, and dermatitis. May cause skin to become dry or cracked.

Eye Contact: Causes permanent damage to the cornea, iris, or conjunctiva. Hydrated lime dust may cause immediate or delayed irritation or inflammation. Eye contact with dry powder or with wet hydrated lime can cause moderate eye irritation, chemical burns and blindness. Eye exposures require immediate first aid and medical attention to prevent significant damage to the eye.

Ingestion: Ingestion may cause adverse effects.

Chronic Symptoms: Long term exposure to respirable crystalline silica results in a significant risk of developing silicosis and other non-malignant respiratory disease, lung cancer, kidney effects, and immune system effects.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Water spray, dry chemical, foam, carbon dioxide.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not considered flammable but may burn at high temperatures.

Explosion Hazard: Product is not explosive.

Reactivity: Hazardous reactions will not occur under normal conditions.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Calcium oxides. Carbon oxides (CO, CO₂). Oxides of magnesium. Silicon oxides.

5.4. Reference to Other Sections

Refer to Section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not handle until all safety precautions have been read and understood. Do not breathe dust. Do not get in eyes, on skin, or on clothing.

6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protective equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

Hydrated Lime

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area.

6.2. Environmental Precautions

Prevent entry to sewers and public waters.

6.3. Methods and Materials for Containment and Cleaning Up

For Containment: Contain solid spills with appropriate barriers and prevent migration and entry into sewers or streams. As an immediate precautionary measure, isolate spill or leak area in all directions.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Recover the product by vacuuming, shoveling or sweeping. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Additional Hazards When Processed: Cutting, crushing or grinding wet or dry lime or other crystalline silica-bearing materials will release respirable crystalline silica. Use all appropriate measures of dust control or suppression, and Personal Protective Equipment (PPE) described in Section 8 below.

Precautions for Safe Handling: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not get in eyes, on skin, or on clothing. Do not breathe dust.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store locked up/in a secure area.

Incompatible Materials: Wet hydrated lime and cement is alkaline and is incompatible with acids, ammonium salts and aluminum metal. Hydrated lime and cement dissolves in hydrofluoric acid, producing corrosive silicon tetrafluoride gas. Hydrated lime and cement reacts with water to form silicates and calcium hydroxide. Silicates react with powerful oxidizers such as fluorine, boron trifluoride, chlorine trifluoride, manganese trifluoride, and oxygen difluoride.

Storage Temperature: Unlimited

7.3. Specific End Use(s)

Hydrated lime is used as an additive for mortar, cement, concrete and concrete products. It is also used in soil stabilization, as an anti-stripping agent in asphalt, for pH adjustment, and in other products that are widely used in construction.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), or Canadian provincial governments.

| Quartz (14808-60-7) | | |
|---------------------|-------------------------|--|
| USA ACGIH | ACGIH OEL TWA | 0.025 mg/m ³ (respirable particulate matter) |
| USA ACGIH | ACGIH chemical category | A2 - Suspected Human Carcinogen |
| USA OSHA | OSHA PEL (TWA) [1] | 50 µg/m ³ (Respirable crystalline silica) |
| USA OSHA | OSHA PEL (TWA) [2] | (250)/(%SiO ₂ +5) mppcf TWA (respirable fraction) (10)/(%SiO ₂ +2) mg/m ³ TWA (respirable fraction) (For any operations or sectors for which the respirable crystalline silica standard, 1910.1053, is stayed or otherwise not in effect, See 20 CFR 1910.1000 TABLE Z-3) |
| USA NIOSH | NIOSH REL (TWA) | 0.05 mg/m ³ (respirable dust) |
| USA IDLH | IDLH | 50 mg/m ³ (respirable dust) |
| Alberta | OEL TWA | 0.025 mg/m ³ (respirable particulate) |

Hydrated Lime

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

| | | |
|------------------------------------|--------------------|--|
| British Columbia | OEL TWA | 0.025 mg/m ³ (respirable) |
| Manitoba | OEL TWA | 0.025 mg/m ³ (respirable particulate matter) |
| New Brunswick | OEL TWA | 0.1 mg/m ³ (respirable fraction) |
| Newfoundland & Labrador | OEL TWA | 0.025 mg/m ³ (respirable particulate matter) |
| Nova Scotia | OEL TWA | 0.025 mg/m ³ (respirable particulate matter) |
| Nunavut | OEL TWA | 0.05 mg/m ³ (respirable fraction (Silica - crystalline)) |
| Northwest Territories | OEL TWA | 0.05 mg/m ³ (respirable fraction (Silica - crystalline)) |
| Ontario | OEL TWA | 0.1 mg/m ³ (designated substances regulation-respirable fraction (Silica, crystalline)) |
| Prince Edward Island | OEL TWA | 0.025 mg/m ³ (respirable particulate matter) |
| Québec | VEMP (OEL TWA) | 0.1 mg/m ³ (respirable dust) |
| Saskatchewan | OEL TWA | 0.05 mg/m ³ (respirable fraction (Silica - crystalline (Trydimite removed))) |
| Yukon | OEL TWA | 300 particle/mL (Silica - Quartz, crystalline) |
| Limestone (1317-65-3) | | |
| USA OSHA | OSHA PEL (TWA) [1] | 15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction) |
| USA NIOSH | NIOSH REL (TWA) | 10 mg/m ³ (total dust) 5 mg/m ³ (respirable dust) |
| Alberta | OEL TWA | 10 mg/m ³ |
| British Columbia | OEL STEL | 20 mg/m ³ (total) |
| British Columbia | OEL TWA | 10 mg/m ³ (total dust) 3 mg/m ³ (respirable fraction) |
| New Brunswick | OEL TWA | 10 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica) |
| Nunavut | OEL STEL | 20 mg/m ³ |
| Nunavut | OEL TWA | 10 mg/m ³ |
| Northwest Territories | OEL STEL | 20 mg/m ³ |
| Northwest Territories | OEL TWA | 10 mg/m ³ |
| Québec | VEMP (OEL TWA) | 10 mg/m ³ (Limestone, containing no Asbestos and <1% Crystalline silica-total dust) |
| Saskatchewan | OEL STEL | 20 mg/m ³ |
| Saskatchewan | OEL TWA | 10 mg/m ³ |
| Yukon | OEL STEL | 20 mg/m ³ |
| Yukon | OEL TWA | 30 mppcf 10 mg/m ³ |
| Calcium oxide (1305-78-8) | | |
| USA ACGIH | ACGIH OEL TWA | 2 mg/m ³ |
| USA OSHA | OSHA PEL (TWA) [1] | 5 mg/m ³ |
| USA NIOSH | NIOSH REL (TWA) | 2 mg/m ³ |
| USA IDLH | IDLH | 25 mg/m ³ |
| Alberta | OEL TWA | 2 mg/m ³ |
| British Columbia | OEL TWA | 2 mg/m ³ |
| Manitoba | OEL TWA | 2 mg/m ³ |
| New Brunswick | OEL TWA | 2 mg/m ³ |
| Newfoundland & Labrador | OEL TWA | 2 mg/m ³ |
| Nova Scotia | OEL TWA | 2 mg/m ³ |
| Nunavut | OEL STEL | 4 mg/m ³ |
| Nunavut | OEL TWA | 2 mg/m ³ |
| Northwest Territories | OEL STEL | 4 mg/m ³ |
| Northwest Territories | OEL TWA | 2 mg/m ³ |
| Ontario | OEL TWA | 2 mg/m ³ |
| Prince Edward Island | OEL TWA | 2 mg/m ³ |

Hydrated Lime

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

| | | |
|--|-------------------------|--|
| Québec | VEMP (OEL TWA) | 2 mg/m ³ |
| Saskatchewan | OEL STEL | 4 mg/m ³ |
| Saskatchewan | OEL TWA | 2 mg/m ³ |
| Yukon | OEL STEL | 4 mg/m ³ |
| Yukon | OEL TWA | 2 mg/m ³ |
| Magnesium oxide (MgO) (1309-48-4) | | |
| USA ACGIH | ACGIH OEL TWA | 10 mg/m ³ (inhalable particulate matter) |
| USA ACGIH | ACGIH chemical category | Not Classifiable as a Human Carcinogen |
| USA OSHA | OSHA PEL (TWA) [1] | 15 mg/m ³ (fume, total particulate) |
| USA IDLH | IDLH | 750 mg/m ³ (fume) |
| Alberta | OEL TWA | 10 mg/m ³ (fume) |
| British Columbia | OEL STEL | 10 mg/m ³ (respirable dust and fume) |
| British Columbia | OEL TWA | 10 mg/m ³ (fume, inhalable) 3 mg/m ³ (respirable dust and fume) |
| Manitoba | OEL TWA | 10 mg/m ³ (inhalable particulate matter) |
| New Brunswick | OEL TWA | 10 mg/m ³ (fume) |
| Newfoundland & Labrador | OEL TWA | 10 mg/m ³ (inhalable particulate matter) |
| Nova Scotia | OEL TWA | 10 mg/m ³ (inhalable particulate matter) |
| Nunavut | OEL STEL | 20 mg/m ³ (inhalable fraction) |
| Nunavut | OEL TWA | 10 mg/m ³ (inhalable fraction) |
| Northwest Territories | OEL STEL | 20 mg/m ³ (inhalable fraction) |
| Northwest Territories | OEL TWA | 10 mg/m ³ (inhalable fraction) |
| Ontario | OEL TWA | 10 mg/m ³ (inhalable particulate matter) |
| Prince Edward Island | OEL TWA | 10 mg/m ³ (inhalable particulate matter) |
| Québec | VEMP (OEL TWA) | 10 mg/m ³ (inhalable dust) |
| Saskatchewan | OEL STEL | 20 mg/m ³ (inhalable fraction) |
| Saskatchewan | OEL TWA | 10 mg/m ³ (inhalable fraction) |
| Yukon | OEL STEL | 10 mg/m ³ (fume) |
| Yukon | OEL TWA | 10 mg/m ³ (fume) |
| Calcium hydroxide (1305-62-0) | | |
| USA ACGIH | ACGIH OEL TWA | 5 mg/m ³ |
| USA OSHA | OSHA PEL (TWA) [1] | 15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction) |
| USA NIOSH | NIOSH REL (TWA) | 5 mg/m ³ |
| Alberta | OEL TWA | 5 mg/m ³ |
| British Columbia | OEL TWA | 5 mg/m ³ |
| Manitoba | OEL TWA | 5 mg/m ³ |
| New Brunswick | OEL TWA | 5 mg/m ³ |
| Newfoundland & Labrador | OEL TWA | 5 mg/m ³ |
| Nova Scotia | OEL TWA | 5 mg/m ³ |
| Nunavut | OEL STEL | 10 mg/m ³ |
| Nunavut | OEL TWA | 5 mg/m ³ |
| Northwest Territories | OEL STEL | 10 mg/m ³ |
| Northwest Territories | OEL TWA | 5 mg/m ³ |
| Ontario | OEL TWA | 5 mg/m ³ |
| Prince Edward Island | OEL TWA | 5 mg/m ³ |
| Québec | VEMP (OEL TWA) | 5 mg/m ³ |
| Saskatchewan | OEL STEL | 10 mg/m ³ |
| Saskatchewan | OEL TWA | 5 mg/m ³ |
| Yukon | OEL STEL | 10 mg/m ³ |
| Yukon | OEL TWA | 5 mg/m ³ |

Hydrated Lime

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

8.2. Exposure Controls

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed.

Personal Protective Equipment: Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.



Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear protective gloves.

Eye and Face Protection: Chemical safety goggles.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

Other Information: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

| | |
|--|-------------------------|
| Physical State | : Solid |
| Appearance | : White or grey powder |
| Odor | : Odorless |
| Odor Threshold | : Not available |
| pH | : 12 – 13 (in water) |
| Evaporation Rate | : Not available |
| Melting Point | : Not available |
| Freezing Point | : Not available |
| Boiling Point | : > 1000 °C (1832 °F) |
| Flash Point | : Not available |
| Auto-ignition Temperature | : Not available |
| Decomposition Temperature | : Not available |
| Flammability (solid, gas) | : Not available |
| Lower Flammable Limit | : Not available |
| Upper Flammable Limit | : Not available |
| Vapor Pressure | : Not available |
| Relative Vapor Density at 20°C | : Not available |
| Relative Density | : 1.9 – 2.4 (water = 1) |
| Specific Gravity | : Not available |
| Solubility | : Negligible. |
| Partition Coefficient: N-Octanol/Water | : Not available |
| Viscosity | : Not available |

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity: Hazardous reactions will not occur under normal conditions.

10.2. Chemical Stability: Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

10.4. Conditions to Avoid: Direct sunlight, extremely high or low temperatures, and incompatible materials.

10.5. Incompatible Materials: Wet hydrated lime and cement is alkaline and is incompatible with acids, ammonium salts and aluminum metal. Hydrated lime and cement dissolves in hydrofluoric acid, producing corrosive silicon tetrafluoride gas. Hydrated lime and cement reacts with water to form silicates and calcium hydroxide. Silicates react with powerful oxidizers such as fluorine, boron trifluoride, chlorine trifluoride, manganese trifluoride, and oxygen difluoride.

Hydrated Lime

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

10.6. Hazardous Decomposition Products: Thermal decomposition may produce: Calcium oxides. Carbon oxides (CO, CO₂). Oxides of magnesium. Silicon oxides.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on Toxicological Effects - Product

Acute Toxicity (Oral): Not classified

Acute Toxicity (Dermal): Not classified

Acute Toxicity (Inhalation): Not classified

LD50 and LC50 Data: Not available

Skin Corrosion/Irritation: Causes skin irritation.

pH: 12 – 13 (in water)

Eye Damage/Irritation: Causes serious eye damage.

pH: 12 – 13 (in water)

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

Carcinogenicity: May cause cancer (Inhalation).

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): May cause respiratory irritation.

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: Irritation of the respiratory tract and the other mucous membranes. Some studies show that exposure to respirable crystalline silica (without silicosis) or that the disease silicosis may be associated with the increased incidence of several autoimmune disorders such as scleroderma (thickening of the skin), systemic lupus erythematosus, rheumatoid arthritis and diseases affecting the kidneys. Silicosis increases the risk of tuberculosis. Some studies show an increased incidence of chronic kidney disease and end-stage renal disease in workers exposed to respirable crystalline silica.

Symptoms/Injuries After Skin Contact: Redness, pain, swelling, itching, burning, dryness, and dermatitis. May cause skin to become dry or cracked.

Symptoms/Injuries After Eye Contact: Causes permanent damage to the cornea, iris, or conjunctiva. Hydrated lime dust may cause immediate or delayed irritation or inflammation. Eye contact with dry powder or with wet hydrated lime can cause moderate eye irritation, chemical burns and blindness. Eye exposures require immediate first aid and medical attention to prevent significant damage to the eye.

Symptoms/Injuries After Ingestion: Ingestion may cause adverse effects.

Chronic Symptoms: Long term exposure to respirable crystalline silica results in a significant risk of developing silicosis and other non-malignant respiratory disease, lung cancer, kidney effects, and immune system effects.

11.2. Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

| | |
|--|--------------|
| Quartz (14808-60-7) | |
| LD50 Oral Rat | > 5000 mg/kg |
| LD50 Dermal Rat | > 5000 mg/kg |
| Calcium oxide (1305-78-8) | |
| LD50 Oral Rat | > 2000 mg/kg |
| LD50 Dermal Rabbit | > 2500 mg/kg |
| Magnesium oxide (MgO) (1309-48-4) | |
| LD50 Oral Rat | 3870 mg/kg |
| Calcium hydroxide (1305-62-0) | |
| LD50 Oral Rat | 7340 mg/kg |
| LD50 Dermal Rat | > 2500 mg/kg |
| Magnesium hydroxide (1309-42-8) | |
| LD50 Oral Rat | 8500 mg/kg |
| Quartz (14808-60-7) | |
| IARC Group | 1 |

Hydrated Lime

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

| | |
|--|---|
| National Toxicology Program (NTP) Status | Known Human Carcinogens. |
| OSHA Hazard Communication Carcinogen List | In OSHA Hazard Communication Carcinogen list. |

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - General: Not classified.

| | |
|--|---|
| Calcium oxide (1305-78-8) | |
| LC50 Fish 1 | 50.6 mg/l |
| Magnesium hydroxide (1309-42-8) | |
| LC50 Fish 1 | 511.31 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static]) |

12.2. Persistence and Degradability

| | |
|--------------------------------------|------------------|
| Hydrated Lime | |
| Persistence and Degradability | Not established. |

12.3. Bioaccumulative Potential

| | |
|--------------------------------------|----------------------|
| Hydrated Lime | |
| Bioaccumulative Potential | Not established. |
| Calcium oxide (1305-78-8) | |
| BCF Fish 1 | (no bioaccumulation) |
| Calcium hydroxide (1305-62-0) | |
| BCF Fish 1 | (no bioaccumulation) |

12.4. Mobility in Soil Not available

12.5. Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste Disposal Recommendations: Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

Ecology - Waste Materials: Avoid release to the environment.

SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

- 14.1. In Accordance with DOT** Not regulated for transport
- 14.2. In Accordance with IMDG** Not regulated for transport
- 14.3. In Accordance with IATA** Not regulated for transport
- 14.4. In Accordance with TDG** Not regulated for transport

SECTION 15: REGULATORY INFORMATION

15.1. US Federal Regulations

| | |
|---|---|
| Hydrated Lime | |
| SARA Section 311/312 Hazard Classes | Health hazard - Skin corrosion or Irritation Health hazard - Serious eye damage or eye irritation Health hazard - Carcinogenicity Health hazard - Specific target organ toxicity (single or repeated exposure) |
| Quartz (14808-60-7) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |
| Limestone (1317-65-3) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |
| Calcium oxide (1305-78-8) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |
| Magnesium oxide (MgO) (1309-48-4) | |

Hydrated Lime

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Calcium hydroxide (1305-62-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Magnesium hydroxide (1309-42-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. US State Regulations

California Proposition 65



WARNING: This product can expose you to Quartz, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

| Chemical Name (CAS No.) | Carcinogenicity | Developmental Toxicity | Female Reproductive Toxicity | Male Reproductive Toxicity |
|-------------------------|-----------------|------------------------|------------------------------|----------------------------|
| Quartz (14808-60-7) | X | | | |

Quartz (14808-60-7)

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

U.S. - Massachusetts - Right To Know List

Limestone (1317-65-3)

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

U.S. - Massachusetts - Right To Know List

Calcium oxide (1305-78-8)

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

U.S. - Massachusetts - Right To Know List

Magnesium oxide (MgO) (1309-48-4)

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

U.S. - Massachusetts - Right To Know List

Calcium hydroxide (1305-62-0)

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

U.S. - Massachusetts - Right To Know List

15.3. Canadian Regulations

Quartz (14808-60-7)

Listed on the Canadian DSL (Domestic Substances List)

Limestone (1317-65-3)

Listed on the Canadian NDSL (Non-Domestic Substances List)

Calcium oxide (1305-78-8)

Listed on the Canadian DSL (Domestic Substances List)

Magnesium oxide (MgO) (1309-48-4)

Listed on the Canadian DSL (Domestic Substances List)

Calcium hydroxide (1305-62-0)

Listed on the Canadian DSL (Domestic Substances List)

Magnesium hydroxide (1309-42-8)

Listed on the Canadian DSL (Domestic Substances List)

Hydrated Lime

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Date of Preparation or Latest Revision : 03/12/2022

Revision

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200 and Canada's Hazardous Products Regulations (HPR) SOR/2015-17.

GHS Full Text Phrases:

| | |
|-------------------|--|
| Aquatic Acute 3 | Hazardous to the aquatic environment - Acute Hazard Category 3 |
| Aquatic Chronic 3 | Hazardous to the aquatic environment - Chronic Hazard Category 3 |
| Carc. 1A | Carcinogenicity Category 1A |
| Eye Dam. 1 | Serious eye damage/eye irritation Category 1 |
| Skin Irrit. 2 | Skin corrosion/irritation Category 2 |
| STOT RE 1 | Specific target organ toxicity (repeated exposure) Category 1 |
| STOT SE 3 | Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation |
| H315 | Causes skin irritation |
| H318 | Causes serious eye damage |
| H335 | May cause respiratory irritation |
| H350 | May cause cancer |
| H372 | Causes damage to organs through prolonged or repeated exposure |
| H402 | Harmful to aquatic life |
| H412 | Harmful to aquatic life with long lasting effects |

Indication of Changes

| Section | Change | Date Changed | Version |
|---------|---|--------------|---------|
| 1 | Modified responsible party information, logo & emergency telephone number | 03/12/2022 | 3.1 |

Holcim US believes the information contained herein is accurate; however, Holcim US makes no guarantees with respect to such accuracy and assumes no liability in connection with the use of the information contained herein which is not intended to be and should not be construed as legal advice or as insuring compliance with any federal, state or local laws or regulations. Any party using this product should review all such laws, rules, or regulations prior to use, including but not limited to US and Canada Federal, Provincial and State regulations.

NO WARRANTY IS MADE, EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR OTHERWISE.

NA GHS SDS 2015 (Can, US)